

Hex Head Spin-On Mandrels For Threaded Eyelet

- For use with coated abrasive flap wheels, non-woven wheels and other finishing wheels which have an external righthand threaded shank



Catalog #	Fits Thread	Shank Dia.	Head Dia.	O.A.L.
QC-1420	1/4"-20	1/4	3/8	1 3/4
QC-1420-4	1/4"-20	1/4	3/8	4
QC-1420-6	1/4"-20	1/4	3/8	6
QC-1420-8	1/4"-20	1/4	3/8	8

Slotted Head Quick Change Mandrels


- Holds abrasive sheets which are secured in slot and rolled around the head
- Excellent for sanding or finishing internal holes
 - Rust proof finish



Catalog #	Slot Dia.	Slot Width	Depth	O.A.L.
SM-3-250	1/4	1/16	3/4	3
SM-4-250	1/4	1/16	3/4	4
SM-6-250	1/4	1/16	3/4	6
SM-8-250	1/4	1/16	3/4	8
SM-10-250	1/4	1/16	3/4	10
SM-12-250	1/4	1/16	3/4	12

Drill Centers & Kit for Dowel & Tenon

- Centers have both external & internal points for marking exact drilling location
 - Provides for precise alignment of dowels & tenon joints
- Steel construction with zinc-plated finish
 - Sold in packs of 10



Catalog #	O.D.	I.D.
TC-014-10	1/4	3/16
TC-516-10	5/16	1/4
TC-038-10	3/8	5/16
TC-012-10	1/2	3/8

Catalog #	Packaging	Description
TC-8	POLY-BAG 8 PC, SET WITH TWO EACH 1/4", 5/16", 3/8", & 1/2"	

Straight Head Spin-On Mandrels For Threaded Eyelet

- These mandrels hold various abrasives and do not require washers or nuts
 - Quick & easy replacement
 - Rust proof black oxide finish



Catalog #	Fits Thread	Shank Dia.	O.A.L.
PM-348-1	#3-48	1/8	2 1/2
PM-348-2	#3-48	1/4	2 1/2
PM-348-2-4	#3-48	1/4	4
PM-348-2-6	#3-48	1/4	6
PM-348-2-8	#3-48	1/4	8
PM-832	#8-32	1/4	3
PM-832-4	#8-32	1/4	4
PM-832-6	#8-32	1/4	6
PM-832-8	#8-32	1/4	8
PM-1420	1/4"-20	1/4	3
PM-1420-QC	1/4"-20	1/4	2
PM-1420-4	1/4"-20	1/4	4
PM-1420-6	1/4"-20	1/4	6
PM-1420-8	1/4"-20	1/4	8

Winding Arbors

- For use in the manufacturing of cartridge rolls



Catalog #	O.D.	Slot Width	Slot Length	O.A.L.
WA-564-1	3/32	0.025	3	4 1/2
WA-564-2	3/32	0.032	3	4 1/2
WA-332-1	7/64	0.025	3	4 1/2
WA-332-2	7/64	0.032	3	4 1/2
WA-332-3	1/8	0.045	3	4 1/2
WA-18-2	9/64	0.032	3	4 1/2
WA-18-3	5/32	0.045	3	4 1/2
WA-18-4	5/32	0.057	3	4 1/2
WA-316-2	13/64	0.032	3	4 1/2
WA-316-3	7/32	0.045	3	4 1/2
WA-316-4	15/64	0.057	3	4 1/2
WA-14-2	17/64	0.032	3	4 1/2
WA-14-3	9/32	0.045	3	4 1/2
WA-14-4	19/64	0.057	3	4 1/2
WA-516-3	11/32	0.045	3	4 1/2
WA-516-4	23/64	0.057	3	4 1/2