



**CLESCO**

"The Abrasive Hardware Specialist"

## Motor & Grinder Shaft Arbors

- Nut Lock Type – for smooth shafts
- For mounting various wheels (buffs, wire brush, non-woven, etc.)
- Arbor is secured to smooth motor shafts with socket set screws
- RH (right-hand) units with 1/2"-20 threaded arbors can also be used to mount Climax keyless chucks to drive various shank-mounted accessories
- Use RH (right-hand) type for counter-clockwise shaft rotation (facing shaft)
- Use LH (left-hand) type for clockwise shaft rotation (facing shaft)

### Type A "Small"

This type is ideal for use on smaller fractional horse-power motors.



Type	Deluxe		Economy		Fits Shaft Dia.	Fits Wheel Hole	Thread	Max Wheel Width	Thread Length	O.A.L.
	Machined	Washer Dia.	Stamped	Washer Dia.						
A	A-320-D	1	A-320	1 1/4	1/4	3/8	R.H.	1/2	1 1/8	2
A	A-325-D	1	A-325	1 1/4	5/16	3/8	R.H.	1/2	1 1/8	2
A	A-330-D	1	A-330	1 1/4	3/8	3/8	R.H.	1/2	1 1/8	2
A			AL-320	1 1/4	1/4	3/8	L.H.	1/2	1 1/8	2
A			AL-325	1 1/4	5/16	3/8	L.H.	1/2	1 1/8	2
A			AL-330	1 1/4	3/8	3/8	L.H.	1/2	1 1/8	2

### Type B "Standard"

These Arbors have a 1/2" diameter threaded portion that is 1-13/16" long which can accommodate wheels up to 1-1/4" wide.



Type	Deluxe		Economy		Fits Shaft Dia.	Fits Wheel Hole	Thread	Max Wheel Width	Thread Length	O.A.L.
	Machined	Washer Dia.	Stamped	Washer Dia.						
B	AS-4	1 1/2	AS-4FS	1 5/8	1/2	1/2	R.H.	1 1/16	1 13/16	3 1/2
B	AS-5	1 1/2	AS-5FS	1 5/8	5/8	1/2	R.H.	1 1/16	1 13/16	3 1/2
B	AL-4	1 1/2	AL-4FS	1 5/8	1/2	1/2	L.H.	1 1/8	1 13/16	3 1/2
B	AL-5	1 1/2	AL-5FS	1 5/8	5/8	1/2	L.H.	1 1/8	1 13/16	3 1/2
B	AL-6	1 1/2	AL-6FS	1 5/8	3/4	1/2	L.H.	1 1/8	1 13/16	3 1/2
B	AL-5-KW*	1 1/2			5/8	1/2	L.H.	1 1/4	1 13/16	3 1/2
B	AS-5-KW*	1 1/2			5/8	1/2	R.H.	1 3/16	1 13/16	3 1/2

\*AL-5-KW and AS-5-KW have a keyway.