



CLESCO

"The Abrasive Hardware Specialist"

Specials

Clesco has the capability to produce custom machined parts & assemblies. Additionally, custom packaging is available. Often a slight modification to our standard product line allows for efficient production to meet your needs. Contact customer service at 1-800-542-6552 with your request.



Maximum RPM Rating for Clesco Sanding Drums

Drum Dia.	Drum Width	Shank Dia.	Max. rpm
1/4"	1/2"	1/8"	30,000
1/4"	3/4"	1/8"	22,000
1/4"	1"	1/8"	20,000
3/8"	1/2"	1/8"	30,000
3/8"	1"	1/8"	18,000
1/2"	1/2"	1/8"	30,000
1/2"	1/2"	1/4"	30,000
1/2"	3/4"	1/8"	18,000
1/2"	3/4"	1/4"	25,000
1/2"	1"	1/4"	20,000
1/2"	1 1/2"	1/4"	14,000
1/2"	2"	1/4"	10,000
5/8"	1/2"	1/4"	27,000

Drum Dia.	Drum Width	Shank Dia.	Max. rpm
5/8"	1"	1/4"	19,000
3/4"	1/2"	1/4"	27,000
3/4"	3/4"	1/4"	24,000
3/4"	1"	1/4"	19,000
3/4"	1 1/2"	1/4"	12,000
3/4"	2"	1/4"	9,000
1"	1/2"	1/4"	18,000
1"	3/4"	1/4"	15,000
1"	1"	1/4"	15,000
1"	1 1/2"	1/4"	10,000
1"	2"	1/4"	8,000
1"	3"	1/4"	5,000
1 1/4"	1"	1/4"	14,000

Drum Dia.	Drum Width	Shank Dia.	Max. rpm
1 1/4"	2"	1/4"	7,000
1 1/2"	1"	1/4"	14,000
1 1/2"	1 1/2"	1/4"	10,000
1 1/2"	2"	1/4"	7,000
2"	1"	1/4"	11,000
2"	1 1/2"	1/4"	8,000
2"	2"	1/4"	6,000
3"	1"	1/4"	3,000
3"	1"	3/8"	3,000
3"	2"	1/4"	3,000
3"	2"	3/8"	3,000
3"	3"	3/8"	3,000

Safety Warning: Power tool accessories and hand tools are dangerous when used improperly. Comply with all safety regulations as set by the American National Standards Institute (ANSI) and Occupational Safety and Health Administration (OSHA). Always protect face, eyes, and body when using hand and power tools.

Disclaimer: Please Note dimensional differences may exist from Manufacturer to Manufacturer. While size may vary slightly, in no way does this effect form, fit or function. For exact product specifications, please contact the factory at 800.542.6552.

Warranty: Clesco, a wholly owned subsidiary of **Climax Metal Products Company**, warrants that all parts listed in this catalog meet the size and material specifications within. Any non-conforming product will be replaced or the purchased price refunded at the Company's option. The user is responsible for determining the suitability of a part for a particular application and performance. No employee of Clesco or its agents has the authority to represent these products for a particular application or use. Clesco's liability is limited to the price of the part and neither Clesco nor the seller's liability shall exceed the price of the part.

www.climaxmetal.com

Phone: 1-800-542-6552 Fax: 1-800-860-5553