

TWO-PIECE CLAMPING COLLARS - 2C-SERIES

Black Oxide Steel	T303 Stainless Steel	Aluminum	Zinc Plated Steel	Bore Size	OD	Width	Clamp Screw	Box Qty	Weight* (Ounce)
2C-012	2C-012-S	2C-012-A		1/8	11/16	5/16	4-40 x 3/8	20	0.43
2C-018	2C-018-S	2C-018-A		3/16	11/16	5/16	4-40 x 3/8	20	0.39
2C-025	2C-025-S	2C-025-A		1/4	11/16	5/16	4-40 x 3/8	20	0.38
2C-031	2C-031-S	2C-031-A		5/16	11/16	5/16	4-40 x 3/8	20	0.34
2C-037	2C-037-S	2C-037-A		3/8	7/8	3/8	6-32 x 3/8	20	0.71
2C-043	2C-043-S	2C-043-A		7/16	15/16	3/8	6-32 x 3/8	20	0.76
2C-050	2C-050-S	2C-050-A	2C-050-Z	1/2	1 1/8	13/32	8-32 x 1/2	20	1.26
2C-056	2C-056-S	2C-056-A		9/16	1 5/16	7/16	10-32 x 1/2	20	2.00
2C-062	2C-062-S	2C-062-A	2C-062-Z	5/8	1 5/16	7/16	10-32 x 1/2	20	1.80
2C-068	2C-068-S	2C-068-A		11/16	1 1/2	1/2	10-32 x 1/2	20	2.80
2C-075	2C-075-S	2C-075-A	2C-075-Z	3/4	1 1/2	1/2	1/4-28 x 5/8	20	2.60
2C-081	2C-081-S	2C-081-A		13/16	1 5/8	1/2	1/4-28 x 5/8	20	3.10
2C-087	2C-087-S	2C-087-A		7/8	1 5/8	1/2	1/4-28 x 5/8	20	2.83
2C-093	2C-093-S	2C-093-A		15/16	1 3/4	1/2	1/4-28 x 5/8	20	3.40
2C-100	2C-100-S	2C-100-A	2C-100-Z	1	1 3/4	1/2	1/4-28 x 5/8	20	3.10
2C-106	2C-106-S	2C-106-A		1 1/16	1 7/8	1/2	1/4-28 x 5/8	10	3.67
2C-112	2C-112-S	2C-112-A		1 1/8	1 7/8	1/2	1/4-28 x 3/4	10	3.50
2C-118	2C-118-S	2C-118-A		1 3/16	2 3/16	1/2	1/4-28 x 3/4	10	4.50
2C-125	2C-125-S	2C-125-A	2C-125-Z	1 1/4	2 3/16	1/2	1/4-28 x 3/4	10	4.22
2C-131	2C-131-S	2C-131-A		1 5/16	2 1/4	9/16	1/4-28 x 3/4	10	5.90
2C-137	2C-137-S	2C-137-A		1 3/8	2 1/4	9/16	1/4-28 x 3/4	10	5.70
2C-143	2C-143-S	2C-143-A		1 7/16	2 1/4	9/16	1/4-28 x 3/4	10	5.23
2C-150	2C-150-S	2C-150-A	2C-150-Z	1 1/2	2 3/8	9/16	1/4-28 x 3/4	10	6.06
2C-156	2C-156-S	2C-156-A		1 9/16	2 3/8	9/16	1/4-28 x 3/4	10	5.61
2C-162	2C-162-S	2C-162-A		1 5/8	2 5/8	11/16	5/16-24 x 1	5	9.31
2C-168	2C-168-S	2C-168-A		1 11/16	2 3/4	11/16	5/16-24 x 1	5	9.86
2C-175	2C-175-S	2C-175-A	2C-175-Z	1 3/4	2 3/4	11/16	5/16-24 x 1	5	11.00
2C-187	2C-187-S	2C-187-A		1 7/8	2 7/8	11/16	5/16-24 x 1	5	10.46
2C-193	2C-193-S	2C-193-A		1 15/16	3	11/16	5/16-24 x 1	5	11.57
2C-200	2C-200-S	2C-200-A	2C-200-Z	2	3	11/16	5/16-24 x 1	5	11.00
2C-212	2C-212-S	2C-212-A		2 1/8	3 1/4	3/4	5/16-24 x 1	5	15.00
2C-218	2C-218-S	2C-218-A	2C-218-Z	2 3/16	3 1/4	3/4	5/16-24 x 1	5	14.00
2C-225	2C-225-S	2C-225-A	2C-225-Z	2 1/4	3 1/4	3/4	5/16-24 x 1	5	13.10
2C-231	2C-231-S	2C-231-A		2 5/16	3 1/2	3/4	5/16-24 x 1	5	15.90
2C-237	2C-237-S	2C-237-A		2 3/8	3 1/2	3/4	5/16-24 x 1	5	15.20
2C-243	2C-243-S	2C-243-A		2 7/16	3 1/2	3/4	5/16-24 x 1	5	15.30
2C-250	2C-250-S	2C-250-A	2C-250-Z	2 1/2	3 3/4	7/8	3/8-24 x 1	5	22.30
2C-262	2C-262-S	2C-262-A		2 5/8	3 7/8	7/8	3/8-24 x 1	5	24.00
2C-268	2C-268-S	2C-268-A		2 11/16	4	7/8	3/8-24 x 1	5	25.00
2C-275	2C-275-S	2C-275-A	2C-275-Z	2 3/4	4	7/8	3/8-24 x 1	5	24.00
2C-287	2C-287-S	2C-287-A	2C-287-Z	2 7/8	4 1/4	7/8	3/8-24 x 1	5	29.00
2C-293	2C-293-S	2C-293-A	2C-293-Z	2 15/16	4 1/4	7/8	3/8-24 x 1	5	26.50
2C-300	2C-300-S	2C-300-A	2C-300-Z	3	4 1/4	7/8	3/8-24 x 1	5	25.80
H2C-318	H2C-318-S			3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
H2C-325	H2C-325-S			3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
H2C-343	H2C-343-S			3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
H2C-350	H2C-350-S			3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
H2C-375				3 3/4	5	7/8	3/8-24 x 1	5	32.00
H2C-393				3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
H2C-400	H2C-400-S			4	5 1/4	7/8	3/8-24 x 1	5	33.00
H2C-425				4 1/4	5 1/2	7/8	3/8-24 x 1	5	35.00
H2C-443				4 7/16	5 3/4	7/8	3/8-24 x 1	5	38.50
H2C-450	H2C-450-S			4 1/2	5 3/4	7/8	3/8-24 x 1	5	36.00
H2C-493	H2C-493-S			4 15/16	6 1/4	7/8	3/8-24 x 1	5	42.50
H2C-500	H2C-500-S			5	6 1/4	7/8	3/8-24 x 1	5	40.10
H2C-525				5 1/4	6 3/4	7/8	3/8-24 x 1	5	42.00
H2C-550	H2C-550-S			5 1/2	6 3/4	7/8	3/8-24 x 1	5	43.30
H2C-593				5 15/16	7 1/4	7/8	3/8-24 x 1	1	50.30
H2C-600				6	7 1/4	7/8	3/8-24 x 1	1	47.60



Design fully engages the shaft without marring. Effective on hard and soft shafts. Easily installed where major disassembly would otherwise be required. Greater axial holding power than set screw or one-piece clamping collars.

* Screw lengths are for steel only.

* Weights are approximate.

* H2C-318 through H2C-600 do not have recessed screws.

* H2C-318-S through H2C-550-S do not have recessed screws.

* Zinc plated steel parts come with stainless steel screws.

DIMENSION
Bore, Inch

TOLERANCE
.003/- .000

CORROSION RESISTANT TWO-PIECE CLAMPING COLLARS - CR2C-SERIES

Steel With Yellow Zinc and 316 Stainless Steel

Yellow Zinc Dichromate	T316 Stainless Steel	Bore Size	OD	Width	Clamp Screw	Box Qty	Weight (Ounce)*
CR2C-050	CR2C-050-S	1/2	1 1/8	13/32	8-32 x 1/2	20	1.260
CR2C-062	CR2C-062-S	5/8	1 5/16	7/16	10-32 x 1/2	20	1.800
CR2C-075	CR2C-075-S	3/4	1 1/2	1/2	1/4-28 x 5/8	20	2.600
CR2C-100	CR2C-100-S	1	1 3/4	1/2	1/4-28 x 5/8	20	3.100
CR2C-125	CR2C-125-S	1 1/4	2 1/16	1/2	1/4-28 x 3/4	10	4.220