



## ONE-PIECE CLAMPING COLLARS RECESSED SCREW - H1C-SERIES

Recessed screw head provides an outside surface free of major projections for safety  
Design fully engages the shaft without marring  
Greater axial holding power than set screw collars  
Effective on hard and soft shafts

Black Oxide Steel	T303 Stainless Steel	Aluminum	Bore Size	OD	Width	Clamp Screw	Box Qty	Weight* (Ounce)
H1C-012	H1C-012-S	H1C-012-A	1/8	13/16	1/4	4-40 x 3/8	20	0.51
H1C-018	H1C-018-S	H1C-018-A	3/16	13/16	1/4	4-40 x 3/8	20	0.50
H1C-025	H1C-025-S	H1C-025-A	1/4	13/16	1/4	4-40 x 3/8	20	0.45
H1C-031	H1C-031-S	H1C-031-A	5/16	13/16	1/4	4-40 x 3/8	20	0.43
H1C-037	H1C-037-S	H1C-037-A	3/8	1 1/16	5/16	6-32 x 3/8	20	0.95
H1C-043	H1C-043-S	H1C-043-A	7/16	1 1/16	5/16	6-32 x 3/8	20	0.92
H1C-050	H1C-050-S	H1C-050-A	1/2	1 1/4	3/8	8-32 x 1/2	20	1.50
H1C-056	H1C-056-S	H1C-056-A	9/16	1 1/4	3/8	8-32 x 1/2	20	1.50
H1C-062	H1C-062-S	H1C-062-A	5/8	1 1/2	13/32	10-32 x 1/2	20	2.40
H1C-068	H1C-068-S	H1C-068-A	11/16	1 1/2	13/32	10-32 x 1/2	20	2.30
H1C-075	H1C-075-S	H1C-075-A	3/4	1 3/4	1/2	1/4-28 x 5/8	20	3.90
H1C-081	H1C-081-S	H1C-081-A	13/16	1 3/4	1/2	1/4-28 x 5/8	20	3.80
H1C-087	H1C-087-S	H1C-087-A	7/8	1 7/8	1/2	1/4-28 x 5/8	20	4.50
H1C-093	H1C-093-S	H1C-093-A	15/16	1 7/8	1/2	1/4-28 x 5/8	20	4.20
H1C-100	H1C-100-S	H1C-100-A	1	2	1/2	1/4-28 x 5/8	20	4.80
H1C-106	H1C-106-S	H1C-106-A	1 1/16	2	1/2	1/4-28 x 5/8	10	4.60
H1C-112	H1C-112-S	H1C-112-A	1 1/8	2 1/8	1/2	1/4-28 x 3/4	10	5.30
H1C-118	H1C-118-S	H1C-118-A	1 3/16	2 1/8	1/2	1/4-28 x 3/4	10	5.00
H1C-125	H1C-125-S	H1C-125-A	1 1/4	2 1/4	1/2	1/4-28 x 3/4	10	5.70
H1C-131	H1C-131-S	H1C-131-A	1 5/16	2 1/4	1/2	1/4-28 x 3/4	10	5.50
H1C-137	H1C-137-S	H1C-137-A	1 3/8	2 3/8	1/2	1/4-28 x 3/4	10	6.20
H1C-143	H1C-143-S	H1C-143-A	1 7/16	2 3/8	1/2	1/4-28 x 3/4	10	5.90
H1C-150	H1C-150-S	H1C-150-A	1 1/2	2 1/2	1/2	1/4-28 x 3/4	10	6.50
H1C-156	H1C-156-S	H1C-156-A	1 9/16	2 1/2	1/2	1/4-28 x 3/4	10	6.20
H1C-162	H1C-162-S	H1C-162-A	1 5/8	3	5/8	5/16-24 x 1	10	13.20
H1C-168	H1C-168-S	H1C-168-A	1 11/16	3	5/8	5/16-24 x 1	5	12.70
H1C-175	H1C-175-S	H1C-175-A	1 3/4	3	5/8	5/16-24 x 1	5	12.10
H1C-187	H1C-187-S	H1C-187-A	1 7/8	3 1/4	5/8	5/16-24 x 1	5	14.60
H1C-193	H1C-193-S	H1C-193-A	1 15/16	3 1/4	5/8	5/16-24 x 1	5	14.00
H1C-200	H1C-200-S	H1C-200-A	2	3 1/4	5/8	5/16-24 x 1	5	13.40
H1C-218			2 3/16	3 1/2	5/8	5/16-24 x 1	5	15.40
H1C-225			2 1/4	3 1/2	5/8	5/16-24 x 1	5	14.90
H1C-237			2 3/8	3 1/2	5/8	5/16-24 x 1	5	13.50
H1C-243			2 7/16	4	3/4	3/8-24 x 1	5	28.30
H1C-250			2 1/2	4	3/4	3/8-24 x 1	5	24.70
H1C-262			2 5/8	4 1/4	3/4	3/8-24 x 1	5	27.70
H1C-268			2 11/16	4 1/4	3/4	3/8-24 x 1	5	26.80
H1C-275			2 3/4	4 1/4	3/4	3/8-24 x 1	5	26.50
H1C-287			2 7/8	4 1/2	3/4	3/8-24 x 1	5	30.30
H1C-293			2 15/16	4 1/2	3/4	3/8-24 x 1	5	29.30
H1C-300			3	4 1/2	3/4	3/8-24 x 1	5	28.30
H1C-318			3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
H1C-325			3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
H1C-343			3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
H1C-350			3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
H1C-393			3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
H1C-400			4	5 1/4	7/8	3/8-24 x 1	5	33.00

DIMENSION	TOLERANCE
Bore, Inch	+.003/-0.000

\* Weights are approximate. H1C-318 through H1C-400 do not have recessed screws. Black oxide steel and aluminum bore sizes 3/4" through 3" do not have a relief cut. Stainless Steel bore sizes 1 9/16" through 3" do not have a relief cut.