



TWO-PIECE CLAMPING COLLARS RECESSED SCREW - H2C-SERIES

Recessed screw head provides an outside surface free of major projection for safety
 Design fully engages the shaft without marring
 Easily installed where major disassembly would otherwise be required
 Greater axial holding power than set screw or one-piece clamping collars
 Effective on hard and soft shafts

Black Oxide Steel	T303 Stainless Steel	Bore Size	OD	Width	Clamp Screw	Box Qty	Weight* (Ounce)
H2C-012	H2C-012-S	1/8	13/16	1/4	4-40 x 3/8	20	0.48
H2C-018	H2C-018-S	3/16	13/16	1/4	4-40 x 3/8	20	0.44
H2C-025	H2C-025-S	1/4	13/16	1/4	4-40 x 3/8	20	0.42
H2C-031	H2C-031-S	5/16	13/16	1/4	4-40 x 3/8	20	0.40
H2C-037	H2C-037-S	3/8	1 1/16	5/16	6-32 x 3/8	20	0.89
H2C-043	H2C-043-S	7/16	1 1/16	5/16	6-32 x 3/8	20	0.83
H2C-050	H2C-050-S	1/2	1 1/4	3/8	8-32 x 1/2	20	1.45
H2C-056	H2C-056-S	9/16	1 1/4	3/8	8-32 x 1/2	20	1.41
H2C-062	H2C-062-S	5/8	1 1/2	13/32	10-32 x 1/2	20	2.20
H2C-068	H2C-068-S	11/16	1 1/2	13/32	10-32 x 1/2	20	2.10
H2C-075	H2C-075-S	3/4	1 3/4	1/2	1/4-28 x 5/8	20	3.60
H2C-081	H2C-081-S	13/16	1 3/4	1/2	1/4-28 x 5/8	20	3.50
H2C-087	H2C-087-S	7/8	1 7/8	1/2	1/4-28 x 5/8	20	4.10
H2C-093	H2C-093-S	15/16	1 7/8	1/2	1/4-28 x 5/8	20	3.90
H2C-100	H2C-100-S	1	2	1/2	1/4-28 x 5/8	20	4.50
H2C-106	H2C-106-S	1 1/16	2	1/2	1/4-28 x 5/8	10	4.30
H2C-112	H2C-112-S	1 1/8	2 1/8	1/2	1/4-28 x 3/4	10	5.00
H2C-118	H2C-118-S	1 3/16	2 1/8	1/2	1/4-28 x 3/4	10	4.70
H2C-125	H2C-125-S	1 1/4	2 1/4	1/2	1/4-28 x 3/4	10	5.30
H2C-131	H2C-131-S	1 5/16	2 1/4	1/2	1/4-28 x 3/4	10	5.00
H2C-137	H2C-137-S	1 3/8	2 3/8	1/2	1/4-28 x 3/4	10	5.80
H2C-143	H2C-143-S	1 7/16	2 3/8	1/2	1/4-28 x 3/4	10	5.50
H2C-150	H2C-150-S	1 1/2	2 1/2	1/2	1/4-28 x 3/4	10	6.20
H2C-156	H2C-156-S	1 9/16	2 1/2	1/2	1/4-28 x 3/4	10	5.80
H2C-162	H2C-162-S	1 5/8	3	5/8	5/16-24 x 1	10	12.50
H2C-168	H2C-168-S	1 11/16	3	5/8	5/16-24 x 1	5	12.10
H2C-175	H2C-175-S	1 3/4	3	5/8	5/16-24 x 1	5	11.50
H2C-187	H2C-187-S	1 7/8	3 1/4	5/8	5/16-24 x 1	5	13.80
H2C-193	H2C-193-S	1 15/16	3 1/4	5/8	5/16-24 x 1	5	13.40
H2C-200	H2C-200-S	2	3 1/4	5/8	5/16-24 x 1	5	12.70
H2C-212	H2C-212-S	2 1/8	3 1/2	5/8	5/16-24 x 1	5	15.00
H2C-218	H2C-218-S	2 3/16	3 1/2	5/8	5/16-24 x 1	5	14.60
H2C-225	H2C-225-S	2 1/4	3 1/2	5/8	5/16-24 x 1	5	14.00
H2C-237		2 3/8	3 1/2	5/8	5/16-24 x 1	5	13.40
H2C-243	H2C-243-S	2 7/16	4	3/4	3/8-24 x 1	5	12.90
H2C-250	H2C-250-S	2 1/2	4	3/4	3/8-24 x 1	5	22.80
H2C-262		2 5/8	4 1/4	3/4	3/8-24 x 1	5	26.60
H2C-268		2 11/16	4 1/4	3/4	3/8-24 x 1	5	26.00
H2C-275		2 3/4	4 1/4	3/4	3/8-24 x 1	5	25.10
H2C-287		2 7/8	4 1/2	3/4	3/8-24 x 1	5	29.00
H2C-293		2 15/16	4 1/2	3/4	3/8-24 x 1	5	28.00
H2C-300	H2C-300-S	3	4 1/2	3/4	3/8-24 x 1	5	26.60
H2C-318	H2C-318-S	3 3/16	4 1/2	7/8	3/8-24 x 1	5	28.30
H2C-325	H2C-325-S	3 1/4	4 1/2	7/8	3/8-24 x 1	5	27.30
H2C-343	H2C-343-S	3 7/16	4 3/4	7/8	3/8-24 x 1	5	31.00
H2C-350	H2C-350-S	3 1/2	4 3/4	7/8	3/8-24 x 1	5	29.10
H2C-375		3 3/4	5	7/8	3/8-24 x 1	5	32.00
H2C-393		3 15/16	5 1/4	7/8	3/8-24 x 1	5	35.00
H2C-400	H2C-400-S	4	5 1/4	7/8	3/8-24 x 1	5	33.00
H2C-425		4 1/4	5 1/2	7/8	3/8-24 x 1	5	35.00
H2C-443		4 7/16	5 3/4	7/8	3/8-24 x 1	5	38.50
H2C-450	H2C-450-S	4 1/2	5 3/4	7/8	3/8-24 x 1	5	36.00
H2C-493	H2C-493-S	4 15/16	6 1/4	7/8	3/8-24 x 1	5	42.50
H2C-500	H2C-500-S	5	6 1/4	7/8	3/8-24 x 1	5	40.10
H2C-525		5 1/4	6 3/4	7/8	3/8-24 x 1	5	42.00
H2C-550	H2C-550-S	5 1/2	6 3/4	7/8	3/8-24 x 1	5	43.30
H2C-593		5 15/16	7 1/4	7/8	3/8-24 x 1	1	50.30
H2C-600		6	7 1/4	7/8	3/8-24 x 1	1	47.60

DIMENSION Bore, Inch	TOLERANCE +.003/-.000
-------------------------	--------------------------

* Weights are approximate
 * H2C-318 through H2C-600 do not have recessed screws
 * H2C-318-S through H2C-550-S do not have recessed screws.

Climax Metal Products Company • www.climaxmetal.com • Phone: 800-542-6552 • Fax: 800-860-5553

TWO-PIECE CLAMPING COLLARS