



METRIC CLAMPING COLLARS
M1C-SERIES AND M2C-SERIES

Design fully engages the shaft without marring or other damage
Two-piece collars are easily installed where major disassembly would otherwise be required
Greater axial holding power than set screw collars
Effective on hard and soft shafts

METRIC CLAMPING COLLARS

Climax Metal Products Company • www.climaxmetal.com • Phone: 800-542-6552 • Fax: 800-860-5553

Black Oxide Steel (1-Piece)	Black Oxide Steel (2-Piece)	Stainless Steel (1-Piece)	Stainless Steel (2-Piece)	Bore Size (mm)	OD (Inch)	Width (mm)	Clamp Screw	Box Qty	Weight* (1-Piece)	Weight* (2-Piece)
M1C-03	M2C-03	M1C-03-S	M2C-03-S	3	11/16	9	M 3 x 8	100	0.40	0.40
M1C-04	M2C-04	M1C-04-S	M2C-04-S	4	11/16	9	M 3 x 8	100	0.40	0.40
M1C-05	M2C-05	M1C-05-S	M2C-05-S	5	11/16	9	M 3 x 8	100	0.41	0.40
M1C-06	M2C-06	M1C-06-S	M2C-06-S	6	3/4	9	M 3 x 8	100	0.48	0.46
M1C-07	M2C-07	M1C-07-S	M2C-07-S	7	3/4	9	M 3 x 8	100	0.47	0.43
M1C-08	M2C-08	M1C-08-S	M2C-08-S	8	1	9	M 3 x 10	100	0.90	0.90
M1C-09	M2C-09	M1C-09-S	M2C-09-S	9	1	9	M 3 x 10	50	1.00	0.81
M1C-10	M2C-10	M1C-10-S	M2C-10-S	10	1	9	M 3 x 10	50	1.36	0.80
M1C-12	M2C-12	M1C-12-S	M2C-12-S	12	1 1/8	11	M 4 x 12	50	1.40	1.31
M1C-13	M2C-13	M1C-13-S	M2C-13-S	13	1 1/4	11	M 4 x 12	50	1.60	1.50
M1C-14	M2C-14	M1C-14-S	M2C-14-S	14	1 1/4	11	M 4 x 12	50	1.60	1.50
M1C-15	M2C-15	M1C-15-S	M2C-15-S	15	1 3/8	13	M 5 x 16	50	2.41	2.30
M1C-16	M2C-16	M1C-16-S	M2C-16-S	16	1 3/8	13	M 5 x 16	50	2.30	2.25
M1C-17	M2C-17	M1C-17-S	M2C-17-S	17	1 1/2	13	M 5 x 16	50	2.60	2.60
M1C-18	M2C-18	M1C-18-S	M2C-18-S	18	1 1/2	13	M 5 x 16	50	2.50	2.40
M1C-19	M2C-19	M1C-19-S	M2C-19-S	19	1 5/8	15	M 6 x 16	50	3.70	3.61
M1C-20	M2C-20	M1C-20-S	M2C-20-S	20	1 5/8	15	M 6 x 16	50	3.60	3.41
M1C-21	M2C-21	M1C-21-S	M2C-21-S	21	1 3/4	15	M 6 x 16	50	4.00	3.90
M1C-22	M2C-22	M1C-22-S	M2C-22-S	22	1 3/4	15	M 6 x 16	25	3.90	3.71
M1C-23	M2C-23	M1C-23-S	M2C-23-S	23	1 7/8	15	M 6 x 16	25	4.60	4.45
M1C-24	M2C-24	M1C-24-S	M2C-24-S	24	1 7/8	15	M 6 x 16	25	4.30	4.20
M1C-25	M2C-25	M1C-25-S	M2C-25-S	25	1 7/8	15	M 6 x 16	25	4.20	4.80
M1C-26	M2C-26			26	2	15	M 6 x 16	25	4.90	4.00
M1C-28	M2C-28			28	2	15	M 6 x 16	25	4.50	4.40
M1C-30	M2C-30	M1C-30-S	M2C-30-S	30	2 1/8	15	M 6 x 16	25	6.11	5.90
M1C-32	M2C-32			32	2 1/8	15	M 6 x 16	25	6.02	5.50
M1C-34	M2C-34			34	2 1/4	15	M 6 x 16	25	6.20	6.11
M1C-35	M2C-35	M1C-35-S	M2C-35-S	35	2 1/4	15	M 6 x 16	25	6.13	5.90
M1C-36	M2C-36			36	2 1/4	15	M 6 x 16	25	5.90	5.70
M1C-38	M2C-38			38	2 3/8	15	M 6 x 16	25	5.90	6.31
M1C-40	M2C-40	M1C-40-S	M2C-40-S	40	2 3/8	15	M 6 x 16	25	5.90	5.70
M1C-42	M2C-42			42	2 7/8	19	M 8 x 25	10	14.00	13.50
M1C-45	M2C-45	M1C-45-S	M2C-45-S	45	2 7/8	19	M 8 x 25	10	12.90	12.50
M1C-48	M2C-48			48	3 1/8	19	M 8 x 25	10	14.80	14.10
M1C-50	M2C-50	M1C-50-S	M2C-50-S	50	3 1/8	19	M 8 x 25	5	13.80	13.50
M1C-54	M2C-54			54	3 1/4	19	M 8 x 25	5	14.90	14.30
M1C-55	M2C-55	M1C-55-S	M2C-55-S	55	3 1/4	19	M 8 x 25	5	14.50	14.00
M1C-60	M2C-60	M1C-60-S	M2C-60-S	60	3 1/2	19	M 8 x 25	5	16.20	15.50
M1C-65	M2C-65	M1C-65-S	M2C-65-S	65	3 3/4	19	M 8 x 25	5	16.80	16.70
M1C-70	M2C-70	M1C-70-S	M2C-70-S	70	4	19	M 8 x 25	5	18.30	17.70
M1C-75	M2C-75	M1C-75-S	M2C-75-S	75	4 1/4	19	M 8 x 25	5	19.50	18.80
M1C-80	M2C-80	M1C-80-S	M2C-80-S	80	4 1/4	19	M 8 x 25	5	20.40	19.70

DIMENSION Bore, mm	TOLERANCE +.08mm/-.00mm
-----------------------	----------------------------

* Weights are approximate
M1C-40 through M1C-80 do not have a relief cut